

**OUR STORM DRAINS FLOW
DIRECTLY TO THE BEACH.**

**PLEASE HELP KEEP THEM
CLEAN!**



BMP D01: Storm Water Conveyance System Inspection and Management

Targeted Pollutants:

- Bacteria
- Metals
- Nutrients
- Oil & Grease
- Organics
- Oxygen Demanding Substances
- Pesticides
- Sediment
- Total Residual Chlorine
- Trash & Debris

Purpose:	To prevent or reduce the discharge of pollutants into the storm water conveyance system.
Application:	Storm drain inlets and the storm water conveyance system (e.g., inlets, culverts, and pipes).
Practices:	<ol style="list-style-type: none"> 1. Mark/label storm drains with "NO DUMPING" vinyl markers (available from EH&S). 2. Ensure personnel are aware that only rain is permitted to go into storm drains. 3. Clean storm drain inlets in high pollutant load areas just before the wet season to remove sediments and debris accumulated during the summer. 4. Inspect storm water conveyance system annually. 5. Store wastes collected from cleaning activities in appropriate containers to prevent discharge to a storm drain. 6. Report dumping or other non-storm water flows into storm drains by calling EH&S: (858) 534-3660. 7. DO NOT store machinery, equipment, or vehicles over storm drains.
Frequency & Maintenance:	<ol style="list-style-type: none"> 1. Conduct visual storm drain inspections annually in high pollutant load areas where sediment, trash, or other pollutants accumulate more often. 2. Clean storm drain conveyance system at least once before the wet season (October – May) and as needed during the wet season. 3. Maintain records of inspections and maintenance. 4. If dry weather flows are observed, notify EH&S at (858) 534-3660 and try to identify and if possible eliminate the source.
Additional Information:	<ul style="list-style-type: none"> • EH&S web pages on Blink: http://blink.ucsd.edu/ehs • EH&S provides Storm Water Pollution Prevention Training: (858) 534-3660

ONLY RAIN IN THE STORM DRAIN!!!

